


FIELD REPORT









CANADA-NEWFOUNDLAND FLOOD DAMAGE REDUCTION PROGRAM

FLOOD RISK MAPPING STUDY GLENWOOD/APPLETON

FIELD REPORT

Prepared by: Haywon Keel

SHAWMONT NEWFOUNDLAND LIMITED P.O. Box 9600 St. John's, Newfoundland A1A 3C1

> Date First Issued: February, 1989 Date Final Issue: August, 1989

TABLE OF CONTENTS

	PAGE
PART ONE - INTRODUCTION	
1.0 INTRODUCTION	1-1
1.1	1-1
1.1.1 Site Inspection 1.1.2 Topographic Survey 1.1.3 Interview Survey 1.1.4 Fall Flood Water Level Program 1.1.5 Other Information	1-1 1-1 1-2 1-2 1-2
1.2 JOB DIARY	1-3
PART TWO - FIELD PROGRAM	
2.0 FIELD PROGRAM AT GLENWOOD/APPLETON	2-1
2.1 SETTING UP	2-1
2.2 RIVER CROSS-SECTIONS	2-1
2.3 VERIFICATION OF AERIAL PHOTO CONTOURS	2-3
2.4 INTERVIEW SURVEY	2-4
TABLES	
FIGURES	
APPENDIX I - BRIDGE PLANS	

PART ONE

INTRODUCTION

1.0 INTRODUCTION

1.1 The major purposes of the field program were:

- to obtain an appreciation of site conditions, as these relate to flood problems, and
- to obtain physical measurements for verification and calibration of analytical models.

The scope of work for this program is outlined in the following paragraphs. Details on the work done and data collected are given in Section 2.

1.1.1 Site Inspection

A site inspection visit by R. Picco of the Department of Environment and Lands, P.C. Helwig and H.J. Keats, SNL was carried out on November 14, 1988. The purpose of the visit was to meet municipal authorities, assess site conditions and to select locations for river cross-sections.

1.1.2 Topographic Survey

No cross-sectional data was available for the Glenwood/Appleton section of the Gander River. After a review of aerial photos, discussions with people familiar with this stretch of the river and a walk-over of the site it was decided that ten cross-sections, including sections at the highway and railway bridges were required for mathematically modelling the river. Temporary bench marks were also established at strategic locations along the river

1.1.2 Topographic Survey (Cont'd)

and the main road in Appleton for use in measuring water levels from a possible fall flood. Information on water levels from historic flood was sought from residents of both Glenwood and Appleton.

1.1.3 Interview Survey

During the field program, local officials and residents were approached informally at their residences. They were informed about the purpose of the study and the methods employed. They were also asked to recollect any information on previous floods that would also be a benefit to the study. House to house interview surveys of residents within flood prone areas were then performed to identify high water levels, as well to note resident's observations on the behaviour of the rivers during past flooding events.

1.1.4 Fall Flood Water Level Program

A local resident of the area was engaged by the surveyor as boatman/rodman and was also instructed on marking water levels.

The plan was to measure water levels for a significant fall (or spring) flood, should such an event occur during the life of the study. Unfortunately no significant event occurred, and this option was not implemented.

1.1.5 Other Information

Plans for the Trans Canada Highway and CNR bridges are provided in Appendix I.

1.2 JOB DIARY

November 15

Weather: Sunny, temperature 3°, light winds in the am, winds started to pick up in the afternoon.

Work Done: Completed all of the river sections.

November 16

Weather: Miserable day - rained the whole day with northerly winds and 1° temperatures.

Work Done: Work progressed very slowly due to the weather. Established bench marks at most of the cross-sections on Gander River.

November 17

Weather: Sunny with cold temperatures, light winds.

Work Done: Measured water elevations at rest of crosssections, picked up most of the historical flood data from the residents of Glenwood. Two more river cross-sections were also done.

November 18

Weather: Miserable day with heavy rain in the morning and cold northerly winds.

Work Done: Obtained the remaining historical flood data in both Glenwood and Appleton. Finished up the field program for Glenwood/Appleton.

PART TWO

FIELD PROGRAM

2.0 FIELD PROGRAM AT GLENWOOD/APPLETON

2.1 SETTING UP

The field program for Glenwood/Appleton was carried out from November 14 to November 18, 1988. The first objective after we had arrived at the site was to do a complete walk-over of the river banks to select optimum locations for river cross-sections. In attendance for the walk-over was a representative of the Department of Environment and Lands, Mr. Robert Picco; the study manager, Mr. Philip Helwig; the surveyor, Mr. Hayward Keats; and a local resident of Appleton, who was familiar with the river, Mr. Danny Stiles. Mr. Stiles was later engaged to serve as a boatman, for the river cross-section survey and as rodman for the water level and historical flood level surveys.

Upon completion of the walk-over, eight cross-sections were located by the study manager. Two additional cross-sections were later requested by the Study Manager, after reviewing the requirements for a HEC-2 model.

Meetings were arranged with the mayors of Appleton and Glenwood, Dr. David Prior and Mrs. Iris Warren, respectively. Both officials were visited at their residences and informed about the purpose of the study. They were also asked for information on past flooding events.

2.2 RIVER CROSS-SECTIONS

A level survey was performed to obtain water elevations at each of the ten cross-sections and to establish temporary bench marks near each cross-section to facilitate a fall

2.2 RIVER CROSS-SECTIONS (Cont'd)

flood level survey. Geodetic bench marks were used for vertical control [a bench marks description and elevation having been obtained form the Department of Crown Lands, surveys division before the field program had begun]. Two bench marks were used, one on the Canadian National Railway bridge, [Monument #50F279K] on the Appleton side, with an elevation of 27.674 m and the other near St. Ann's Church, [Monument #76F395] on the Glenwood side, with an elevation of 31.662 m. The bench mark survey was a complete loop with a closure error of 0.005 m in a traverse distance of 3.8 km, which meets the normal standards for second order level transfer.

Sections 1-5, 7 and 9, were measured using a depth sounder. These sections were initially marked on a 1:2500 scale map during the walk-over and were subsequently relocated and aligned with the advice of the boatman. The boatman controlled alignment by steering towards a series of range poles that were placed on the opposite bank of the river such that they were in the boatman's view at all times.

A Sitex, Model HE203-MK2 depth sounder was used with the transducer securely strapped to the side of the river boat. For traversing the boatman would start as close as possible to the water's edge (typically 1 to 2 meters from shore), and maintain a constant speed and direction. Coordination of this aspect of the work involved close cooperation of boatman and surveyor. Elapsed time, distance travelled and cross-section identification were recorded on the depth sounder tape to facilitate data reduction. Three traverses were made at each section and data reduced each evening. Comparison of the cross-section plots enable a check to be

2.2 RIVER CROSS-SECTIONS (Cont'd)

performed on accuracy of the work. Satisfactory agreement was obtained at all cross-sections. No resurveys were required. Water surface width were measured by stadia. Calibration checks on the depth sounder were made at the start and finish of each day's work. One test was made in shallow water and a second test in deep water, both of known depth. No significant changes in the calibration factor were observed.

Table 2.1 summarizes the bench marks elevations established during the field program. River cross-section data is summarized in Table 2.2 to 2.11, and plotted up to Figure 2.1 to 2.11. Figure 2.12 shows cross-section locates.

Water levels were established at each of the river section from each of the temporary bench marks that were set out during the bench mark transfer survey. Flows measure at Big Chute (2YQ001) remained essentially constant from day to day, as below:

Date		Dai	ly Flow
Nov.	16	107	m^3/s
Nov.	17	109	m^3/s
Nov.	18	117	$m^{3/s}$

2.3 VERIFICATION OF AERIAL PHOTO CONTOURS

Difficulties were encountered in extending cross-section lines, as requested in the Terms of Reference. The main difficulty being necessity of cutting lines across private property. Experience on other ShawMont projects indicated ground contours can be established with the desired accuracy

2.3 VERIFICATION OF AERIAL PHOTO CONTOURS (Cont'd)

 $(\pm~0.3~\text{m})$ by photogrammetric mapping based on low level photography. Accordingly it was decided that the objectives of the Terms of Reference could be achieved if the accuracy of the map contours could be verified allowing on land cross-section to be determined from base mapping contours. Elevations shown on the maps were checked at strategic points as below:

Location	Map Elevation	Field Elevation
Highway Bridge	30.4	30.514
East Abutment		
Vertical Control Point	30.0	29.924
V-21		
Vertical Control Point	28.4	28.342
V-1		

2.4 INTERVIEW SURVEY

During the field survey some of the residents in the flood prone areas were questioned about past flood events. They were asked to indicate to the best of their recollection the height reached by flood waters during the 1983 flood and any other floods that they could remember. These elevations were duly record and used in the calibration of the HEC 2 model.

Data collected in this survey is plotted on base mapping of the study area (in envelope package at end of the report). A collection of photos of the 1983 flood is shown in Figures 2.13 and 2.14.

LIST OF TABLES

TABLE	2.1	Bench Ma	ark	El	evations	
TABLE	2.2	Section	1	- X	Section	Data
Table	2.3	Section	2	- X	Section	Data
Table	2.4	Section	3	- X	Section	Data
Table	2.5	Section	4	- X	Section	Data
Table	2.6	Section	5	- X	Section	Data
Table	2.7	Section	6	- X	Section	Data
Table	2.8	Section	7	- X	Section	Data
Table	2.9	Section	8	- X	Section	Data
Table	2.10	Section	9	- X	Section	Data
Table	2.11	Section	10	-	X Section	Data
Table	2.12	Section	11	-	X Section	Data

TABLE 2.1
BENCH MARK LOCATIONS

B.M. #'s	ELEVATION	REMARKS
BM #1	27.674	Geodetic Bench Mark #50F279K - Appleton
TBM #1	31.164	Top of Hydrant Near Ford Simms
TBM #2	33.934	House - Appleton Top of I-Beam South Entrance - Dave
TBM #3	34.474	Parrot's Driveway - Appleton Spike in Hydro Pole on Salmon River
TBM #4	31.534	Road - Appleton Spike in Guy Pole #4645 Near Lou
TBM #4.5	30.704	Marche's Cabin - Appleton Spike in Guy Pole \$4688 Near
TBM #5	28.564	Maidment's Garage - Appleton Top of Concrete Wall at Pumphouse -
TBM #6	30.744	Appleton East Abutment D/S Side of Queen
		Elizabeth Bridge - Glenwood
TBM #7	30.729	West Abutment D/S Side of Queen Elizabeth Bridge - Glenwood
TBM #8	29.509	Base of Municipal Pump Near Robert Coates - Glenwood
TBM #9	27.129	Top of Rock 30 m From Shore Near
BM #2	31.662	Cross-Section 10 - Glenwood Geodetic Bench Mark #76F395 -
TBM #10	28.842	Glenwood Top of Hydrant Corner of Adams and Main - Glenwood

Section #1 Mater level = 25.389 FLOW (M^3/S) = 109

TABLE 2.2

25.389 25.389 25.389 25.389 ELEVATION 25,389 25,389 WATER 22.34 22.43 22.64 23.29.64 24.25.39 27.20 27.20 30.20 Elevation (Geodetic) 970. 970. 970. 970. 970. 980. 1000 ELEVATION 25,389 25.389 25.389 25.389 25.389 25.389 25.389 25.389 25.389 25.389 25.389 25.389 25.389 25,389 25.389 25.389 25.389 25, 389 25.389 25,389 25.389 25, 389 25,389 25,389 25,389 25, 389 25, 389 25.389 25, 389 25.389 25.389 25.389 25, 389 25.389 25.389 25.389 25, 389 23.21 22.86 22.78 22.51 22.51 20.69 20.69 20.60 20.42 23.39 20.69 20.25 20.34 20.08 Elevation (Geodetic) 21.64 21.64 21.38 20.95 20.69 19.81 19.73 19.55 19.55 19.29 19.55 19.73 06.61 20.77 19.47 19.47 19.81 19.73 19.47 19.47 19.47 20.77 20.77 20.86 500 520 530 540 550 560 570 580 590 900 610 620 630 ELEVATION 255.0889 255.0889 255.0889 255.0889 255.0889 255.0889 255.0889 25.389 25.339 25.339 25.389 25, 389 25,389 25,339 WATER 20.20 29.40 29.40 29.75 29.75 29.20 29.30 29.30 29.30 29.30 29.30 29.30 29.30 27.65 27.75 21.99 22.25 22. 43 22. 43 23. 43 24. 15 24. 15 (Geodetic) 22.08 21.99 21.91 Elevation 22.17 21.91 22.51 58885554 080 200 210

4			,	
(•	1	1	
	Ĺ		1	
	ABI	1		
	É		4	

Section # 2 Water Level=25.379 FLOW (M^3/S) = 109

Elevation

E E E E E E E E E E E E E E E E E E E	MATER ELEVATION 25.379 25.379 25.379 25.379 25.379 25.379 25.379 25.379 25.379 25.379 25.379 25.379 25.379	8 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	December 1	ELEVATION	STA 40 30 10 0	Elevation (Seodetic) 29.40 29.50 29.50 29.50 30.50	WATER ELEVATION
---------------------------------------	---	---	------------	-----------	----------------------------	--	--------------------

Section # 3 Water Level=25.359 FLOW $(M^3/S) = 109$

					220 0 7	1.10
20045-000	Elevation			ATT. TANK	Elevation	
STA.	(Geodetic)	ELEVATION		STA.	(Geodetic)	FLEVALIUM
740	30.50			310	26.70	
730	29.40			300	26.90	
720	28.80			290	27.10	
710	28.50			280	27.40	
700	28.20			270	27.40	
690	27.50			260	27.30	
680	27.00			250	27.40	
670	25.80			240	27.40	
660	26.60			230	27.40	
450	26.20			220	27.40	
640	25.80			210	27.80	
630	25.50			200	28.10	
620	25.20	25.359		190	28.10	
610	25.30	25.359		180	28.10	
600	24.14	25.359		170	28.30	
590	23.62	25.359	r	160	28.10	
580	23.62	25.359		150	28.15	
570	23.09	25.359		140	28.20	
550	22.83	25.359		130	28.25	
550	22.83	25.359		120	28.30	
540	22.92	25.359		110	28.35	
530	23.09	25.359		100	28.40	
520	23.36	25.359		90	28.45	
510	23.62	25.359		80	28.50	
500	23.79	25.359		70	29.00	
490	24.66	25.359		60	29.10	
480	25.01	25.359		50	29.20	
470	24.90	25.359		40	29.40	
460	25.20	25.359		30	29.55	
450	25.40	25.359		20	29.70	
440	26.00	20.007		10	29.90	
430	27.10			0	30.00	
420	27.20			- 8		
410	27.00					
400	26.80					
390	26.60			6		
380	26.40					
370	26.30					
360	26.20					
350	26.35					
340	26.50					
330	26.40					
320	26.40					14
and the fact	20.40					

Section # 4 Water Level=25.334 $FLOW (M^3/S) = 109$

П		Elevation	WATER		Elevation	WATER
100	STA.	(Geodetic)	ELEVATION	STA.	(Geodetic)	ELEVATION
	660	30.00		230	27.30	
-	650	29.30		220	27.50	
	640	28.90		210	27.60	
-	630	28.65		200	27.70	
-	620	28.40		190	27.80	
	610	27.90		180	28.10	
-	600	27.35		170	28.40	
	590	26.80		160	28.10	
	580	26.30		150	28.20	
	570	25.50		140	28.25	
	560	24.64	25.334	130	28.30	
-	550	24.29	25.334	120	28.40	
	540	23.94	25.334	110	28.50	
_	530	23.85	25.334	100	28.70	
-	520	23.77	25.334	90	28.85	
-	510	23.77	25.334	80	29.00	
	500	23.94	25.334	70	29.15	
	490	23.94	25.334	60	29.30	
	480	24.20	25.334	50	29.40	
-	470	24.20	25.334	40	29.50	
	460	24.20	25.334	20	29.60	
100	450	24.46	25.334	20	29.75	
-	440	25.50		10	29.85	
	430	25.40		0	30.10	
100	420	25.90				
7	410	26.10				
-	400	26.50				
_	390	26.60				
	380	26.50				
100	370	25.50				
	350	25.40				
	350	25.30				
	340	25.60				
	330	24.70				
100	320	24.70	22			
10.	310	24.70				
_	200	25.00				
-	290	25.50				
	280	25.50				
	270	25.90				
	260	26.25				
	250	26.70				
1	240	27.00				

Section # 5 Water Level=24.999 FLOW (M^3/S) = 109

	Elevation	WATER	
STA	(Geodetic)		
570	30.35		
560	29.95		
550	29.60		
540	29.25		
530	29.00		
520	28.75		
510	28.25	174.7	
500	27.80		
490	27.50		
480			
470	26.75		
450	26.00		
450		24.999	
440		24.999	
430		24.999	
420		24.999	
410		24.999	
400		24.999	
390		24.999	
380		24.999	
370	22.73		
360	22.82		
350	23.87		
340	25.00		
330	25.50		
320	25.70		
310	25.50		
300	25.00		
290			
280	23.26		
270	22.82		
260	22.12		
250	22.47		
240	22.56		
230	23.08		
220	25.00		
210	25.70		
200	26.00		
190	26.60		
180	27.00		
170	27.25		
160	27.40		
150	27.70		

Elevation	WATER
(Geodetic)	ELEVATION
27.85	
28.25	
28.50	
28.90	
28.60	
29.10	
29,20	
29.20	
29.20	
29.20	
29.00	
28.90	
29.00	
29.00	
30.00	
	(Geodetic) 27.85 28.25 28.50 28.90 29.40 29.20 29.20 29.20 29.20 29.00 28.90 29.00

Section # 6 at CN Bridge Water Level=24.479 FLOW (M^3/S) = 109

	Elevation	
STA.	(Geodetic)	ELEVATION
370	30.05	
360	29.90	
350	29.80	
340	29.70	
330	29.50	
320	29.49	
310	29.47	
300	29.44	
290	29.41	
280	29.38	
270	29.34	
260	29.31	
250	29.28	
240	29.25	
230	29.22	
	29.19	
220	29.16	
210		
200	29.13	
200	28.03	
199	26.13	
195	25.13	
190	24.03	
185	23.63	
180	23.73	
175	23.73	
170	23.83	
165	24.13	24.479
161	24.48	
161	27.88	
159	27.88	
159	24.38	
155	23.38	
150	23.43	24.479
145	23.38	
140	22.93	24.479
135	22.13	24.479
130	22.88	24.479
125	23.13	24.479
121	24.48	
121	27.88	
119	27.88	
118	24.03	24.479
115		24.479
110	المال و لد لد	- 10 10 1

	Elevation	WATER
STA.	(Geodetic)	ELEVATION
110	21.83	24.479
105	22.88	24.479
100	23.63	24.479
95	23.88	24.479
90	24.38	
85	25.53	
81	26.38	
81	28.03	
80	29.13	
70	29.20	
60	29.30	
50	29.40	
40	29.50.	
30	29.65	
20	29.75	
10	29.85	
0	30.05	

Section # 7 Water Level=24.224 FLOW (M^3/S) = 109

ŕ		Elevation	WATER
ŀ	STA.	(Geodetic)	ELEVATION
	320	30.50	
r	310	29.00	
ı	300	29.50	
-	290	29.00	
	280	23.90	
ı	270	28.80	
ŀ.	260	28.65	
	250	28.60	
ı	240	27.90	
ı	230	27.75	
	220	27.60	
r	210	27.45	
ı	200	26.95	
7	190	24.25	
	180	22.57	24.224
ı	170	22.31	24.224
В.	160	22.05	
	150	21.87	24.224
ı	140	21.96	
ı,	130	22.05	
	120	22.13	
ı	110	23.61	24.224
ŀ	100	25.70	
	90	25.40	
ı	80.	26.00	
ŀ	70	25.00	
	60	25.00	
	50	27.00	
ı	40	28.10	
ò	30	28.25	
	20	28.40	
ľ	10	28.75	
	0	30.00	

Section # 8 at TCH Bridge

TABLE 2.9

Water Level=24.221 FLOW (M^3/S) = 109

*	Elevation	WATER
STA.	(Geodetic)	
128	30.72	
128	25.47	
123	24.52	
118		24.221
113		24.221
108	22.22	24.221
103	21.87	24.221
102	22.07	24.221
101	30.98	
99		
99		24.221
98	22.62	24.221
93	22.62 23.49	24.221
88	23.25	
83	23.32	24.221
78	23.09	24.221
73	23.35	
68	22.92	24.221
66		24.221
65		
63	31.39	
63	22.99 22.99	24.221
63		
58	23.35	
53	23.57	
48	23.29	
43	23.35	24.221
38	23.32	24.221
33		24.221
30		24.221
29	31.10	
27	31.08	24.221
27		
23 18	23.42	
13	23.70 23.99	24.221
12	24.22	24.221
0		27.221
0	30.71	
U	30171	

Section # 9 Water Level=24.024 $FLDW (M^3/S) = 109$

		LIATES			F1	MATER
	Elevation	WATER		5.T.A	Elevation	
STA.	(Geodetic)	ELEVALIUN		STA.	(Geodetic)	ELEVATION
620	30.25			190	26.75	
610	29.95			180	27.50	
600	29.80			170	27.50	
590	29.70			150	27.50	
580	29.50			150	28.10	
570	29.40			140	28.60	
560	29.25			130	28.75	
550	29.10			120	29.00	
540	28.90			110	29.00	
530	28.85			100	29.70	•
520	28.80			90	29.50	
510	28.70			80	29.60	
500	28.60			70	29.65	1941)
490	28.50			60	29.70	
480	28.30			50	29.75	
470	28.15			40	29.80	
460	27.95			30	29.90	
450	27.80			20	30.00	
440	27.70			10	30.00	
430	27.60			0	30.10	
420	27.40		0			
410	27.25					
400	26.80					
390	26.60					
380	26.25					
370	25.80					
360	25.25					
350	24.02	24.024				
340	22.46	24.024				
330	22.11	24.024				
320	21.59	24.024				
310	21.32	24.024				
300	20.98	24.024				
290	21.15	24.024				
280	20.98	24.024				
270	21.41	24.024				
260	21.67	24.024			Ø.	
250	21.93	24.024				
240	22.37	24.024				
230	21.67	24.024				
220	22.80	24.024				
	24.02	24.024				
210		24.024				
200	25.75				3	

Section # 10 Water Level=24.024 FLOW (M $^3/$ S) = 109


STA.	Elevation (Geodetic) 30.00	WATER ELEVATION		STA. 50	Elevation (Geodetic) 28.90	WATER ELEVATION
480				40	29.10	
470	29.60			30	29.25	
460	29.60			20	29.40	*
450	29.60			10	29.50	
440	29.60			0	30.10	26
430	29.50				00.10	ă.
420	29.50					
410	29.40					
400	29.40					
390	29.25					
380	29.10					
370	29.10					
360	29.10					
350	29.00					
340	28.75					
330	28.40					
320	28.25					
310	28.20					
300	28.00					
290	27.75					
280	27.50 26.50					
270	25.00					
250	24.40					
250	24.20					*
240	22.02					
230	21.50					
220	21.24		<i>c</i>			
210	21.24					
200	21.24					
190 180	21.06					
170	21.32					
160	21.24					
150	22.02		20			
140	22.28		Jg.			
130	22.89					
120	23.15					
110	23.59					
100	25.25					
90	25.70					
80						
70	27.00					
50	27.90					


Section # 11 Water Level=23.5 FLOW $(M^3/S) = 109$

	Elevation	
STA.	(Geodetic)	ELEVATION
0	30	
250	23.5	23.5
276	22.7	23.5
310	22.7	23.5
335	23.5	23.5
425	30	


LIST OF FIGURES

Figure	2.1	Cross-Section Locations
Figure	2.2	Section #1
Figure	2.3	Section #2
Figure	2.4	Section #3
Figure	2.5	Section #4
Figure	2.6	Section #5
Figure	2.7	Section #6
Figure	2.8	Section #7
Figure	2.9	Section #8
Figure	2.10	Section #9
Figure	2.11	Section #10
Figure	2.12	Selected Photos 1983 Flood
Figure	2.13	Selected Photos 1983 Flood











- 1. Elevations are geodetic
- 2. Cross-sections are plotted looking downstream
- 3. Water levels at time of survey



- Elevations are geodetic
- Cross-sections are plotted looking downstream Water levels at time of survey


FIGURE 2.3




- 1. Elevations are geodetic
- 2. Cross-sections are plotted looking downstream
- 3. Water levels at time of survey

FIGURE 2.4







- 1. Elevations are geodetic
- 2. Cross-sections are plotted looking downstream
- 3. Water levels at time of survey







- 1. Elevations are geodetic
- 2. Cross-sections are plotted looking downstream
- 3. Water levels at time of survey




- 1.
- Elevations are geodetic Cross-sections are plotted looking downstream 2.
- Water levels at time of survey 3.

FIGURE 2.7




Gander River




- Elevations are geodetic
- 2. Cross-sections are plotted looking downstream
- 3. Water levels at time of survey







- Elevations are geodetic
- Cross-sections are plotted looking downstream Water levels at time of survey 2.



- 1. Elevations are geodetic
- 2. Cross-sections are plotted looking downstream
- 3. Water levels at time of survey





- 1. Elevations are geodetic
- 2. Cross-sections are plotted looking downstream
- 3. Water levels at time of survey

The Flood of 1983

THE residents of Glenwood were taken by surprise on January 14, 1983, when they awoke to find Gander Lake approximately eleven feet above its normal level. The following photos speak for themselves.



Elam Gillingham pulls his boat along Main Street.

> Why not tie the riverboat up to the woodshed?



